



# TANDBERG 880

For medium- to small-sized meeting rooms as well as shared office environments. Incorporates the features and functions of larger systems in a portable, high performance set-top box.



Add a PC card for the greater portability of wireless LAN connectivity.

#### DESIGN FEATURES

- Designed for medium to small meeting rooms and shared office environments
- Elegantly designed all-in-one set-top unit that fits easily on any standard television monitor
- Integrated wide angle view camera with extensive zoom, pan and tilt
- Optional cart and monitors

#### APPLICATION FEATURES

- Join up to 4 video sites and 1 audio site with embedded MultiSite functionality
- Powerful live presentations through one-step PC plug-in (PC Presenter) or LAN connection (PC *SoftPresenter*)
- View presentations and presenter simultaneously with either DuoVideo or H.239 on single or dual monitor setup

#### PERFORMANCE FEATURES

- Choice of network: IP up to 1152 kbps, optionally with ISDN up to 384 kbps or with V.35 up to 384 kbps
- PC card slot for wireless LAN connection
- Superior video quality incorporating the H.264 standard
- Highest level of standards-based embedded encryption (AES) is included
- Protection against network interruptions with automatic Downsampling and IPLR

#### UNIT DELIVERED COMPLETE WITH:

Wireless remote control, W.A.V.E. II camera, microphone, and cables

#### BANDWIDTH

H.323 up to 1152 kbps  
H.320 up to 384 kbps

#### VIDEO STANDARDS

H.261, H.263, H.263+, H.263++ (Natural Video), H.264

#### VIDEO FEATURES

Picture in Picture (PIP)  
Intelligent Video Management

#### VIDEO INPUTS (4 INPUTS)

Built-in main camera  
1 x MiniDin, S-video; auxiliary / document camera  
1 x RCA / Phono, composite; document camera/aux  
1 x RCA / Phono, composite; VCR  
1 x XGA: PC

#### VIDEO OUTPUTS (4 OUTPUTS)

1 x MiniDin, S-video; main monitor  
1 x RCA / Phono, composite; main monitor or VCR  
1 x RCA / Phono, composite; dual monitor or VCR  
1 x XGA: main monitor or dual monitor

#### XGA INPUT / XGA OUTPUT

Input: 640 x 480 – 1024 x 768, 56 – 85 Hz. auto-detection  
Output: 640 x 480 – 1024 x 768, 60 Hz

#### VIDEO FORMAT

NTSC, PAL, VGA, SVGA or XGA

#### LIVE VIDEO RESOLUTION

##### NATIVE NTSC:

4SIF (704 x 480 pixels), Digital Clarity  
Interlaced SIF (352 x 480 pixels), Natural Video  
SIF (352 x 240 pixels)

##### NATIVE PAL:

4CIF (704 x 576 pixels), Digital Clarity  
Interlaced CIF (352 x 576 pixels), Natural Video  
CIF (352 x 288 pixels)  
QCIF (176 x 144 pixels)  
SQCIF (128 x 96 pixels) decode only

##### NATIVE PC RESOLUTIONS:

XGA (1024 x 768 pixels)  
SVGA (800 x 600 pixels)  
VGA (640 x 480 pixels)

#### STILL IMAGE TRANSFER

CIF, SIF, 4CIF (H.261 Annex D), 4SIF, VGA, SVGA, XGA

#### AUDIO STANDARDS

G.711, G.722, G.722.1, G.728

#### AUDIO FEATURES

Telephone add-on via MultiSite  
Audio level meters  
Automatic noise reduction  
Two separate acoustic echo cancellers  
Audio mixer  
Automatic gain control  
VCR ducking

#### AUDIO INPUTS (4 INPUTS)

2 x microphone, 11V phantom powered, XLR connector  
1 x RCA / Phono, Line Level; auxiliary  
1 x RCA / Phono, Line Level; VCR

#### AUDIO OUTPUTS (2 OUTPUTS)

1 x RCA / Phono, Line Level; main audio  
1 x RCA / Phono, Line Level; VCR

#### FRAME RATES – POINT-TO-POINT & MULTISITE

15 frames per second @ 56 – 128 kbps  
30 frames per second @ 168 kbps and above  
60 fields per second @ 336 kbps and above,  
Point-to-Point Only (Natural Video)

#### MULTISITE FEATURES

Support for ISDN or IP telephones  
ISDN & IP Downspeeding at call set-up  
Dial in / Dial out capabilities  
Continuous Presence or Voice Switched  
Chair control for host system  
5 sites including min. 1 telephone call  
Built-in MultiSite audio bridge for up to 5 sites  
Built-in MultiSite IP audio bridge for up to 4 sites  
DuoVideo, Digital Clarity  
**MULTISITE (H.243) CASCADING OVER ISDN AND IP**  
Up to 10 video and 4 audio sites  
Any combination of IP & ISDN connections (transcoding)

##### MULTISITE OVER IP

4 sites @ 384 kbps + 1 telephone call over ISDN  
3 sites @ 512 kbps + 2 telephone calls over ISDN  
Point-to-point @ 1152 kbps + 3 telephone calls over ISDN

##### MULTISITE OVER ISDN BRI AND IP

4 sites (1 on ISDN) @ 384 kbps  
4 sites (1 on ISDN) @ 320 kbps + 1 telephone call over ISDN  
3 sites (1 on ISDN) @ 256 kbps + 2 telephone calls over ISDN  
4 sites (2 on ISDN) @ 192 kbps  
4 sites (all ISDN) @ 128 kbps  
3 sites (all ISDN) @ 128 kbps + 2 telephone calls over ISDN  
Point-to-point (ISDN) @ 192 kbps + 3 telephone calls over ISDN

#### DUOVIDEO / H.239

Available on all networks  
Presenter and presentation on single or dual monitor

#### NETWORK FEATURES

Auto H.320 / H.323 dialing  
Downspeeding  
Programmable network profiles  
Intelligent Call Management  
Maximum call length timer  
Automatic SPID and line number configuration (National ISDN, GR-2941-CORE)  
SoftMux

#### EMBEDDED ENCRYPTION

H.320 and H.323 point-to-point and multipoint calls  
Standards-based: H.233, H.234, H.235, DES and AES  
NIST-validated AES  
NIST-validated DES  
Automatic key generation and exchange  
Supported in DuoVideo and H.239

#### H.323 NETWORK FEATURES

Differentiated Services (DiffServ)  
Resource Reservation Protocol (RSVP)  
IP precedence  
IP type of service (ToS)  
Network Address Translation (NAT) Support  
IP adaptive bandwidth management (including flow control)  
Auto gatekeeper discovery  
Dynamic playout and lipsync buffering  
Intelligent Packet Loss Recovery (IPLR)  
IP Address Conflict Warning

#### SECURITY FEATURES

Encrypted IP Password  
Menu Password  
Access code  
Streaming password  
H.243 MCU password  
VNC password  
SNMP security alert  
Encrypted HTTP password  
Possibility to disable IP services

#### NETWORK INTERFACES

3 x ISDN BRI (RJ-45), S-interface  
1 x LAN / Ethernet (RJ-45) 10/100 Mbit (LAN / DSL / cable modem)  
1 x PC card slot (PCMCIA) for wireless LAN

#### WIRELESS LAN SUPPORT

Compliant with IEEE 802.11b, up to 11 Mbit  
Support for 64 / 128 bit encryption (WEP)  
Infrastructure or ad-hoc mode

#### ETHERNET / INTERNET / INTRANET CONNECTIVITY

TCP / IP, DHCP, ARP, FTP, Telnet, HTTP  
SNMP Enterprise Management  
Internal web server  
Internal streaming server (streams local and far-end site)  
10/100 Mbit full / half duplex (manual or auto detect selection)

#### OTHER MAJOR ITU STANDARDS SUPPORTED

H.231, H.233, H.234, H.235, H.235 v2&v3, H.239, H.241, H.243, H.281, BONDING (ISO 13871), H.320, H.323

#### W.A.V.E. (WIDE ANGLE VIEW) II CAMERA

10 x zoom  
1/4" CCD  
+15° / -20° tilt  
+ / -95° pan  
61° vertical field of view  
96° total vertical field of view  
77° horizontal field of view  
267° total horizontal field of view  
460 (PAL) / 470 (NTSC) TV lines  
Min. illumination 2 Lux (F1.8)  
Auto or manual focus / brightness / white balance  
Far-end camera control  
15 near and far-end camera pre-sets  
Voice-activated camera positioning

#### PRESENTATIONS AND COLLABORATION

Natural Presenter Package including:  
PC Presenter  
PC SoftPresenter  
Digital Clarity  
DuoVideo and H.239  
T.120 Microsoft® NetMeeting® support via RS-232 (9-pin D-sub)  
Streaming (compatible with Cisco IP / TV, Apple QuickTime®, RealPlayer® v8 etc.)

#### CLOSED CAPTIONING/TEXT CHAT

T.140 standards-based

#### SYSTEM MANAGEMENT

Support for the TANDBERG Management Suite  
Total management via embedded web server, SNMP, Telnet and FTP  
Remote software upload: during a call over all networks, via webserver or via FTP server  
1 x RS-232 for local software upgrades, local control and diagnostics  
Remote control and on-screen menu system

#### DIRECTORY SERVICES

Searchable server directory\* 50.000+ entries supporting LDAP and H.350  
400 number global directory  
100 number local directory  
16 dedicated MultiSite entries

#### 11 SELECTABLE MENU LANGUAGES

Chinese, English, French, German, Italian, Japanese, Norwegian, Portuguese, Russian, Spanish and Swedish

#### CUSTOMIZED BOOT UP LOGO (JPEG)

#### POWER

Auto-sensing power supply  
100 – 250 VAC, 50 – 60 Hz  
40 watts max.

#### UNIT DIMENSIONS

Height: 5.1" / 13.0cm  
Width: 14.9" / 38.0cm  
Depth: 7.9" / 20.0cm  
Weight: 5.0lbs / 2.3kg

\* Requires TANDBERG Management Suite 9.0 or newer

System features vary depending on network selection and software package. All specifications subject to change without notice.



The TANDBERG 880 has been tested in accordance with interoperability criteria set by Cisco Systems, Inc. and is compatible with the Cisco IP/VC 35XX product family, Cisco MCM 12.1 (5) XM3 and Cisco Aironet Wireless LAN Adapter 350 series. For full disclaimer see TANDBERG product documentation or the following Web site: [www.tandberg.net](http://www.tandberg.net).

TANDBERG is a registered trademark or trademark of TANDBERG in the U.S. and other countries.

Cisco, Cisco Systems, the Cisco Systems logo, and the Cisco Arrow logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

RealPlayer is a trademark or a registered trademark of RealNetworks, Inc.

QuickTime is a registered trademark of Apple Computer, Inc., registered in the U.S. and other countries.

Microsoft and NetMeeting are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

All other trademarks are property of their respective owners.

## TANDBERG

# 880

TANDBERG WORLD HEADQUARTERS  
Philip Pedersens vei 22  
1366 Lysaker, Norway  
Tel: +47 67 125 125  
Fax: +47 67 125 234  
Video: +47 67 117 777  
E-mail: [tandberg@tandberg.net](mailto:tandberg@tandberg.net)

200 Park Avenue, Suite 2005  
New York, NY U.S.A. 10166  
Tel: +1 212 692 6500  
Tel: +1 800 538 2884 (toll free in the U.S.)  
Fax: +1 212 692 6501  
Video: +1 212 692 6535  
E-mail: [tandberg@tandbergusa.com](mailto:tandberg@tandbergusa.com)

June 2004